

PRODUCT COMPARISON CHART

HID® Prox

125 kHz Proximity - Credentials

| Base Part Number | 1326 | 1386 | 1336 | 1597 | 1598 | 202X/212X; 203X/213X | 1431 | 169 | 1346 | 1391 | 1351 | |
|---|-----------------------|---------------------------------|-------|--|------------|-------------------------|--|-----------------------|-----------------------|-----------------------|--------------------|----|
| Read Range: * | | | | | | | | | | | | |
| ProxPoint® Plus | Up to 3.0" (7.5 cm) | | | Up to 2.5" (6.5 cm) | | | | Up to 1.0" (2.5 cm) | Up to 1.5" (4.0 cm) | Up to 2.0" (5.0 cm) | N/A | |
| MiniProx® | Up to 5.5" (14.0 cm) | | | Up to 5.0" (12.5 cm) | | | | Up to 2.0" (5.0 cm) | | Up to 2.5" (6.5 cm) | N/A | |
| Thinline® II | Up to 5.5" (14.0 cm) | | | Up to 5.0" (12.5 cm) | | | | Up to 1.5" (4.0 cm) | Up to 2.0" (5.0 cm) | Up to 3.0" (7.5 cm) | N/A | |
| ProxPro® | Up to 8.0" (20.5 cm) | | | Up to 7.0" (18.0 cm) | | | | Up to 3.0" (7.5 cm) | | Up to 4.0" (10.0 cm) | N/A | |
| ProxPro® II | Up to 9.0" (23.0 cm) | | | Up to 8.0" (20.0 cm) | | | | Up to 4.0" (10.2 cm) | | Up to 4.5" (11.5 cm) | N/A | |
| MaxiProx® | Up to 29.0" (74.0 cm) | | | Up to 20.0" (51.0 cm) | | | | Up to 13.0" (33.0 cm) | Up to 12.0" (28.0 cm) | Up to 15.0" (38.0 cm) | Up to 6.0" (1.8 m) | |
| EntryProx™ | Up to 3.0" (7.5 cm) | | | Up to 2.5" (6.5 cm) | | | | Up to 1.0" (2.5 cm) | Up to 1.5" (4.0 cm) | Up to 2.0" (5.0 cm) | N/A | |
| Prox80™ | Up to 5.5" (14.0 cm) | Up to 5.0" (12.5 cm) | | Up to 2.5" (6.0 cm) | | Up to 5.0" (12.5 cm) | | Up to 1.5" (3.5 cm) | Up to 2.0" (5.0 cm) | Up to 2.5" (6.0 cm) | N/A | |
| Memory Size/ Application Area | N/A | | | 2k bits with two application areas; 16k bits with two application areas, 16k bits with 16 application areas; 32k bits (16k/2+16k/1), 32k bits (16k/16+16k/1) | | | MIFARE 1K: 1K Byte (8k bits) in 16 64-byte Sectors MIFARE 4K: 4K Byte (32k bits) in 40 Sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes. | N/A | | | | |
| HID Proximity 125 kHz | Yes | | | | | | | | | | | |
| Contact Smart Chip Module Embeddable | No | | Yes** | | Optional** | | | No | | | | |
| Wiegand Strip | No | | | | | | | Yes | | No | | |
| Magnetic Stripe | No | Yes | No | Yes | Optional | | | | | | | No |
| Printable *** | No | Yes | | | | | | | | | No | |
| Slot Punch | Vertical (standard) | Horizontal or Vertical Optional | | Vertical Optional | | | Horizontal or Vertical Optional | | Key Ring Hole | No | | |
| Visual Security Options | N/A | | | Yes | | | | | N/A | | | |
| Warranty | Lifetime | | | | | | | | | | One Year | |

Finding what you need

For security managers, dealers, integrators and OEMs, HID proximity credentials are recognized as the industry standard for physical access control. Featuring 125 kHz RFID technology, HID proximity products are robust, affordable and seamlessly integrate with access control systems.

© 2017 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, and the Chain Design, are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2016-12-21-pacs-prox-credentials-cc-en PLT-03187

* Dependant upon installation conditions.

** Contact smart chip module not included. Ask about HID's SMARTS Program for off-the-shelf contact smart chip embedded cards.

*** Some types of printing processes can take these credentials out of ISO compliance for thickness. Consult factory for more information.